

### ZonEX Pallet Truck Scale in Mild Steel MT IND226X Industrial Indicator

The EuroScales ZonEx pallet truck scale suitable for Zone 1, 21, 2 and 22 applications with an ATEX rating of II (2)G [EEx ib] IIC T4, II (2)D Ex tD A21 IP66 T60 °C. This indicator has a clear 7-segment 6 digits 30mm LED with indicators to show what state the scale is in e.g. motion, kg, lb, gross, net and center of zero. Also with it having a LED readout the battery life is extended to over 70hours in continuous use. Made stronger than the original truck all of the EuroScales range of trucks will take knocks that might well see others fall by the wayside. All EuroScales weighing machines are made using high quality load cells that have an excellent repeatability. EuroScales ZonEx pts is a Heavy duty pallet truck scale, combining time proven durable design with the latest innovations in industrial weighing. High Accuracy Scale 0.1% of the applied load with a capacity of the original truck.

(other display resolutions available)

Choice of 3 widths 450mm, 520mm and 685mm and 4 lengths 910mm, 1000mm, 1150mm and 1220mm.

Other custom sizes available upon request. Closed height of the pallet truck scale is maintained at 85mm.

Supplied calibrated and ready to use with removable / rechargeable battery and safe area mains charger.

The MT IND226X comes with an external battery. Fast update rates for filling make them ideal for use in process applications or for simple weighing.

User friendly ergonomic design that doesn't require the operator to constantly bend down to press the keys



## Performance

### Resolution

Analogue: 3000e OIML; weighing ranges : single range

### Keypad

Hardcoated polyester overlay, 6keys, tactile-feel keypad

### Housing

Full stainless steel enclosure 220mm (w) x 132mm (d) x 148mm (h)

### Protection

IP65 dust and water ingress rating

Hazardous Rating

ATEX: II 2G Ex ib IIC T4 (Gas), II 2D Ex tD A21 IP66 T60°C (Dust)

Digital

Display

LCD, 6 Digit, 30mm high

Power Input

External battery

II 2G Ex ib IIC T5, II 2D Ex ib D21 T93°C IP66 External battery

Charger

Safe area charger 230 VAC

Pallet truck unit

Load cells

IP67 sealed stainless steel load cells—Flintec SLB 1000 C3 / R60 ATEX approved

Standard finish

Sprayed to match the original colour scheme of the truck used

Construction

Welded Mild Steel with stainless steel forks

Size

As ordered

Warranty

5 years on loadcells

Wheels

Anti Static wheels fitted to load or pump depending on truck ordered