

**Weighbeams Mild Steel - MT IND226x Atex Zones 1, 21, 2 and 22**

Capacity 3000kg x 0.5kg graduation with a high Accuracy Scale 0.1% of the applied load The EuroScales Weighbeams are designed for portability and can be re-sited and up and running again in minutes.

Their low profile design make them especially easy to load by manual hand pallet trucks. The MT IND226x is designed for simple weighing applications in hazardous areas, it has three available power sources: an external battery, 230v Power supply unit and 120v Power supply unit.



**Performance**

Resolution	Max 30,000 divisions, weighing ranges : single range
Keypad	Hardcoated polyester overlay, 6 keys, tactile-feel

Housing

Full stainless steel enclosure 220mm (w) x 148mm (d) x 132mm (h)

Protection

IP66 dust and water ingress rating

Hazardous Rating

ATEX: II 2 G EEx ib IIC T4 (Gas), II 2 D Ex tD A21 IP66 T60°C (Dust)

**Digital**

Display	7-segmented LED, 6 Digit, 30mm high
<b>Power Input</b>	
External Battery	Stainless steel housing, NIMH cells 8Ah, includes 3m cable
230 Mains Supply	230 VAC Power supply unit
120 Mains supply	120 VAC Power supply unit
<b>Weighbeams</b>	
Loadcells	IP67 sealed stainless steel load cells - Flintec SLB 1000 C3 / R60 approved
Standard finish	Smooth steel finish / high quality paint finish in blue grey RAL 7031
Construction	Heavy duty folded mild steel construction
Size	1200mm long + handle, width 120mm, height 60mm
Cables	Standard cables 2.5M length with Amphenol plugs
Warranty	5 years on loadcells
Feet	Weights and Measures certified loadcell mounts, passive zinc plated